



Classic R90 featuring black louvers.

STANDARD FEATURES

- EPA Certified
- Single rod air control
- High performance brick-lined firebox
- Clean glass airwash system
- Black cast iron double doors
- Ceramic glass
- Andirons
- Outside air kit

OPTIONS

- Black louvers
- Variable speed blower
- Ash drawer
- Screen door
- Gravity air vent kit
- HeatWave™ kit (Canada only)
- 8" - 7" flue adaptor (Canada only)
- 8" Air cooled pipe adaptors (US only)

SPECIFICATIONS

SPECIFICATIONS	R90
Maximum BTU*	70,000
Typical Sq. Ft. Heated**	1,000 - 2,200
Optimum Efficiency	77.4%
Maximum Log Size	20"
Burn Time (Typical)*	up to 8 hrs.
Emissions (grams/hour)	3.72 g
Firebox Size	2.5 cu. ft.
Flue Size	8"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

*** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.





Excalibur[®] EX90 shown with Excalibur front in black.

STANDARD FEATURES

- EPA Certified
- Single rod air control
- High performance brick-lined firebox
- Clean glass airwash system
- Black cast iron double doors
- Ceramic glass
- Andirons
- Outside air kit

OPTIONS

- Excalibur arch front in black
- Variable speed blower
- Ash drawer
- Screen door
- Gravity air vent kit
- HeatWave™ kit (Canada only)
- 8" - 7" flue adaptor (Canada only)
- 8" Air cooled pipe adaptors (US only)

SPECIFICATIONS

SPECIFICATIONS	EX90
Maximum BTU*	70,000
Typical Sq. Ft. Heated**	1,000 - 2,200
Optimum Efficiency	77.4%
Maximum Log Size	20"
Burn Time (Typical)*	up to 8 hrs.
Emissions (grams/hour)	3.72 g
Firebox Size	2.5 cu. ft.
Flue Size	8"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.

